



## Smart 2590v2



### Profile

Powered by Intel CPU, Smart 2590v2 is designed to support CPU-intensive and graphic demanding applications delivering smooth and outstanding performance in the standalone and virtual desktop environment



# Features

## 01 Powerful SoC performance

New generation Intel CPU drives up to superior digital media performance and rich HD entertainment.

## 02 Multiple VDI protocol supported

Widely supports Citrix ICA/HDX, VMware PCoIP and Microsoft RDP.

## 03 Enhanced Peripherals Applications

Combined with self-developed international patents software SEP, solve problems using USB peripherals in VDI / HSD environment, supports both standalone mode

And multi-user mode

## 04 Convenient Management

By Smart management software, you can achieve rapid deployment of cloud Client. Through centralized management, unified deployment and distribution of Software to help IT administrators significantly reduce maintenance work

## 05 Low TCO solution

Low price, low power consumption and centralized management greatly reduces TCO

## 06 Environment friendly

Low CO2 emission, low heat emission, noise-free and space saving.

# Connectivity



- 1 Power Button
- 2 Line Out
- 3 Mic In
- 4 USB Port
- 5 Power Input

- 6 USB
- 7 LAN
- 8 DVI
- 9 DP
- 10 USB Port



# Specification

Processor	CPU	Intel SoC Dual-Core 2.0GHz
Memory	RAM	2GB DDR3L (Support up to 8GB)
Storage	mSATA	16GB mSATA (Support upto 120GB )
Display	Interface	1x DP, 1x DVI-I (DVI-I can be split to DVI-D + VGA)
	Resolution	DVI-D Up to 1920x1200@60Hz , VGA/DP Up to 2560x1600@60Hz
	Color Depth	Up to 32 bits True Color
	Dual Display	Support Duplicate and Extended Mode
I/O	USB	1x USB 3.0 (Front), 5x USB 2.0 (Rear)
Peripheral	AUDIO	1x Audio Out, 1x Sound In
	POWER	1x DC Power In, 1x Power Switch
Networking	LAN	1x 10/100/1000 Mbps Base-T Fast Ethernet RJ-45
	Wireless	1x 802.11 b/g/n Wireless module ( Optional)
Physical	Dimension	131mm x 31.5mm x 167mm (without mounting kit)
Charateristics	Weight	0.58 kg
Power	Adapter	External 12V/3A DC Adapter
	Consumption	< 10w
Environment	Cooling	Fan-less Convection
	Operation Temp.	0°C to 40°C
	Relative Humidity	30% to 90% non-condensing
Mounting	VESA Bracket	VESA Mounting KIT
	Kensington Lock	Built-in Kensington securityslot



smart 2590V2  
Thin Client





smart 2590V2  
Thin Client

# Contact

## SURENDRANAGAR

2nd Floor, Manivir Complex,  
Vitthal Press Road, Surendranagar.  
Pin 363001,  
Gujarat, INDIA.  
Cell. : +91 982 420 8213  
+91 937 465 1621,  
E-mail : sales@smartstation.in

## AHMEDABAD

Apurva Computers Technologies Pvt Ltd  
1210, 12th Floor, One World West,  
Bopal Approach BRTS Bus stop,  
Near Vakil Saheb Bridge,  
Bopal, Ahmedabad - 380058  
Cell. : +91 982 420 8213  
+91 937 465 1621,  
E-mail : sales@smartstation.in

